

True®

REFRIGERATION

MADE WITH
INNOVATION
IN THE USA



D DESIGN
DEPOT

MILE 3 PHILIP GOLDSON HIGHWAY, BELIZE CITY | 223-3768



REACH-IN REFRIGERATION

T-23-HC

Reach-In Solid Swing Door Refrigerator with Hydrocarbon Refrigerant

- True's solid door reach-ins are designed with enduring quality that protects your longterm investment.
- Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.
- High capacity, factory balanced refrigeration system that maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C) for the best in food preservation.
- Stainless steel solid door and front. Adjustable, heavy duty PVC coated shelves. The finest stainless available with higher tensile strength for fewer dents and scratches.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & 0.02 (3) global warming potential (GWP).

7210-60-9001

Doors	Shelves	Width	Depth	Height*	Voltage	Crated Weight
1	3	27"	29 1/2"	78 3/8"	115/60/1	270 lbs.

* Height does not include 5" for castors or 6" for optional legs



REACH-IN REFRIGERATION

T-23G-HC~FGD01

Reach-In Glass Swing Door Refrigerator with Hydrocarbon Refrigerant~Framed Glass Door Version 01

- True's glass door reach-ins are designed with enduring quality that protects your long-term investment.
- Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace
- High capacity, factory balanced refrigeration system that maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C) for the best in food preservation.
- Energy efficient, "Low-E", double pane thermal glass door.
- Adjustable, heavy duty PVC coated shelves. The finest stainless available with higher tensile strength for fewer dents and scratches.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydro carbon refrigerant that has zero (0) ozone depletion potential (ODP), & 0.02 global warming potential (GWP)..

7210-60-9002

Doors	Shelves	Width	Depth †	Height *	Voltage	Crated Weight
1	3	27"	29 7/8"	78 3/8"	115/60/1	315 lbs.

† Depth does not include 13/8" for door handle.

* Height does not include 5" for castors or 6" for optional legs



MILE 3 PHILIP GOLDSON HIGHWAY, BELIZE CITY | 223-3768



REACH-IN REFRIGERATION

T-49-HC

Reach-In Solid Swing Door Refrigerator with Hydrocarbon Refrigerant



- True's solid door reach-ins are designed with enduring quality that protects your longterm investment
- Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.
- High capacity, factory balanced refrigeration system that maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C) for the best in food preservation.
- Stainless steel solid door and front. Adjustable, heavy duty PVC coated shelves. The finest stainless available with higher tensile strength for fewer dents and scratches.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & 0.02 global warming potential (GWP).

7210-60-9003

Doors	Shelves	Width	Depth	Height*	Voltage	Crated Weight
2	6	54 1/8"	29 1/2"	78 3/8"	115/60/1	425 lbs.

* Height does not include 5" for castors or 6" for optional legs

REACH-IN REFRIGERATION

T-49FG-HC~FGD01

Reach-In Glass Swing Door -10°F Freezer with Hydrocarbon Refrigerant~Framed Glass Door Version 01

- True's glass door reach-ins are designed with enduring quality that protects your long-term investment.
- Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.
- High capacity, factory balanced refrigeration system that maintains -10°F (-23.3°C) temperatures. Ideal for both frozen foods and ice cream.
- Triple pane thermal glass doors. Adjustable, heavy duty PVC coated shelves. The finest stainless available with higher tensile strength for fewer dents and scratches.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- Automatic defrost system time-initiated, temperature-terminated. Saves energy consumption and provides shortest possible defrost cycle.

7210-60-9004



Doors	Shelves	Width	Depth †	Height *	Voltage	Crated Weight
2	6	54 1/8"	29 3/4"	78 3/8"	115/60/1	650 lbs.

† Depth does not include 1 3/8" for door handle.

* Height does not include 5" for castors or 6" for optional legs



MILE 3 PHILIP GOLDSON HIGHWAY, BELIZE CITY | 223-3768





REACH-IN REFRIGERATION

T-23F-HC

Reach-In Solid Swing Door Freezer with Hydrocarbon Refrigerant

- True's solid door reach-ins are designed with enduring quality that protects your longterm investment.
- Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.
- Extra large evaporator coil balanced with higher horsepower compressor and large condenser maintains -10°F (-23.3°C) cabinet temperatures. Ideally suited for both frozen foods and ice cream.
- Stainless steel solid door and front. Adjustable, heavy duty PVC coated shelves. The finest stainless available with higher tensile strength for fewer dents and scratches.
- Automatic defrost system time-initiated, temperature-terminated. Saves energy consumption and provides shortest possible defrost cycle.

7210-60-9005

Doors	Shelves	Width	Depth	Height*	Voltage	Crated Weight
1	3	27"	29 1/2"	78 3/8"	115/60/1	295 lbs.

* Height does not include 5" for castors or 6" for optional legs

REACH-IN REFRIGERATION

T-49F-HC

Reach-In Solid Swing Door Freezer with Hydrocarbon Refrigerant

- True's solid door reach-ins are designed with enduring quality that protects your longterm investment.
- Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.
- Extra large evaporator coil balanced with higher horsepower compressor and large condenser maintains -10°F (-23.3°C) cabinet temperatures. Ideally suited for both frozen foods and ice cream.
- Stainless steel solid door and front. Adjustable, heavy duty PVC coated shelves. The finest stainless available with higher tensile strength for fewer dents and scratches
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).

7210-60-9006



Doors	Shelves	Width	Depth	Height*	Voltage	Crated Weight
2	6	54 1/8"	29 1/2"	78 3/8"	115/60/1	480 lbs.

* Height does not include 5" for castors or 6" for optional legs



REACH-IN REFRIGERATION

T-49G-HC~FGD01

Reach-In Glass Swing Door Refrigerator with Hydrocarbon Refrigerant ~ Framed Glass Door Version 01

- True's glass door reach-ins are designed with enduring quality that protects your long-term investment.
- Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.
- High capacity, factory balanced refrigeration system that maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C) for the best in food preservation.
- Energy efficient, "Low-E", double pane thermal glass doors. Adjustable, heavy duty PVC coated shelves. The finest stainless available with higher tensile strength for fewer dents and scratches.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).

7210-60-9007

Doors	Shelves	Width	Depth †	Height *	Voltage	Crated Weight
2	6	54 1/4"	29 7/8"	78 3/8"	115/60/1	465 lbs.

† Depth does not include 1 5/8" for door handles or 1/2" for system mechanical components.

* Height does not include 5" for castors or 6" for optional legs.



MILE 3 PHILIP GOLDSON HIGHWAY, BELIZE CITY | 223-3768



CHEF BASES

TRCB-52-HC

Drawered Refrigerator with Hydrocarbon Refrigerant



- True's refrigerated chef bases are designed with enduring quality that protects your longterm investment.
- Designed using the highest quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.
- Extra large evaporator coil balanced with higher horsepower compressor and large condenser; maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C) for the best in food preservation.
- Cabinet top is one-piece, heavy duty reinforced stainless steel. Drip resistant "V" edge protects against spills. Supports up to 717 lbs. (326 kg).
- All stainless steel front, top and sides. Corrosion resistant GalFan coated steel back.
- Each drawer accommodates three (3) full size 12"L x 20"W x 4"D (305 mm x 508 mm x 102 mm) food pans (sold separately).
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & 0.02 global warming potential (GWP).

7210-60-9008

Drawers	Width	Depth †	Height *	Voltage	Crated Weight
2	51 7/8"	32 1/8"	20 1/2"	115/60/1	350 lbs.

† Depth does not include 1" for rear bumpers.

* Height does not include 5" for castors or 6" for optional legs.

FOOD PREP TABLES

TSSU-27-08-HC

Solid Door Sandwich/Salad Unit with Hydrocarbon Refrigerant



- True's salad/sandwich units are designed with enduring quality that protects your longterm investment.
- Stainless steel, patented, foam insulated lid and hood keep pan temperatures colder, lock in freshness and minimize condensation. Removable for easy cleaning.
- All stainless steel front, top and ends. Corrosion resistant GalFan coated steel back.
- Interior - attractive, clear coated aluminum liner. Stainless steel floor with coved corners. Heavy duty PVC coated wire shelves.
- Patented forced-air design holds 33°F to 41°F (.5°C to 5°C) product temperature in food pans and cabinet interior.
- 113/4" (299 mm) deep, 1/2" (13 mm) thick, full length removable cutting board included. Sanitary, high density, white polyethylene provides tough preparation surface.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), and 0.02 global warming potential (GWP).

7210-60-9009

Doors	Shelves	Pans (top)	Width	Depth †	Height *	Voltage	Crated Weight
1	2	8	27 5/8"	30 1/8"	36 3/4"	115/60/1	225 lbs.

† Depth does not include 1" for rear bumpers.

* Height does not include 6 1/4" for castors or 6" for optional legs



MILE 3 PHILIP GOLDSON HIGHWAY, BELIZE CITY | 223-3768



UNDERCOUNTERS & WORKTOPS

TWT-48-HC

Solid Door Refrigerator with Hydrocarbon Refrigerant



- True's worktop units are designed with enduring quality that protects your long-term investment.
- All hydrocarbon front, top and ends. Corrosion resistant GalFan coated steel back. Top and backsplash are one piece formed construction. Bacteria and food particles cannot be trapped underneath as with other two-piece worktop units.
- Oversized, environmentally friendly forced-air refrigeration system holds 33°F to 38°F (.5°C to 3.3°C).
- Interior - attractive, clear coated aluminum liner. Stainless steel floor with coved corners. Heavy duty PVC coated wire shelves.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).

7210-60-9010

Doors	Shelves	Width	Depth †	Height *	Voltage	Crated Weight
2	4	48 3/8"	30 1/8"	33 3/8"	115/60/1	280 lbs.

† Depth does not include 1" for rear bumpers and 1/4" for front bumper.

* Height does not include 6 1/4" for castors or 6" for optional legs.



COMMERCIAL ICE MACHINES

TCIM-430

Modular Cubed Ice Machines

- Produces up to 447 lbs. of ice per 24 hours
- Environmentally friendly R290 refrigeration system for optimum ice production and energy efficiency - Up to 37% below Energy Star standards.
- Advanced Control with Touch Screen: 4.3" front display - largest in the industry
- TrueGuard Antimicrobial embedded in every plastic piece including bin liners.
- Simple 1-touch cleaning.
- Easily removable air filter with RCU technology.

7210-60-9011

Doors	Width	Depth	Height	Voltage	@ 70°F air / 50°F water	@ 90°F air / 70°F water	Crated Weight
1	30"	24"	22"	115/60/1	447 lbs. / 24hr.	376 lbs. / 24hr	180 lbs.

COMMERCIAL ICE MACHINES

TIB-530

Modular Ice Storage Bins



- Tru-tech aluminum exterior with heavy duty plastic lid and frame
- All plastic interior plus 100% antimicrobial plastic liner
- Fully insulated with environmentally friendly high-density polyurethane foam
- Slow Close Lid/Hinge design
- Removable Ice Baffle
- Magnascoop[®] included for easy ice scoop storage

7210-60-9012

Capacity	Width	Depth	Height	Voltage	Crated Weight
450 lbs.	30"	34"	50"	115/60/1	175 lbs.

truve®
R E F R I G E R A T I O N

D DESIGN
DEPOT

MILE 3 PHILIP GOLDSON HIGHWAY,
BELIZE CITY | 223-3768